

# STREAMLINER TR

Streamliner is a performance driven made-to-measure profile. Available for recessed, surface mounted or suspended application – down, up or down-up light effect and choice in an SBL or prismatic polycarbonate optic for low glare. Besides evenly illuminated lines, Streamliner can also be equipped with single or clustered Spy modules, downlight modules, an emergency unit or wireless control dimming. To further reduce your energy consumption, either a presence or a daylight sensor can be added to the profile. In addition, Streamliner can also be provided with tunable white LED arrays. In this way Streamliner can be programmed to follow the rhythm of natural daylight, enhancing the wellbeing of the people spending their days in the artificial light of this versatile profile.

[www.deltalight.com/streamlinertr](http://www.deltalight.com/streamlinertr)



1

## PROFILE CONSTRUCTION

<b>SRL TR - PROFILE</b>	<b>SRL TR - END CAP</b>	<b>SRL 85/TR - CORNER 180°</b>	<b>SRL 85/TR - CORNER 90°</b>
389 04 00 00 ◊	389 04 03 01 ◊	389 03 06 01	389 03 06 06
◊ ANO MAX.L / PROFILE: 6m 2,1 / m	◊ ANO 0,1	0,3	0,2

PRO

2

## PROFILE FIXATION

<b>SRL TR - CLIP</b>
389 04 14 01
90 x (L + 10) x 125 min.6 / max.25
0,1

3

## PROFILE CONNECTION

4

## LIGHT MODULES

SEE PAGE PRO 842-845